

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : Rescoset 10 CR TR-D3  
CAS-No. : Mixture  
Product code : 7102  
Other means of identification : Alumina-Silicate Wet Chemically Bonded Mortar-Slurry

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory  
Recommended use : Industrial use

#### 1.3. Supplier

Resco Products, Inc.  
One Robinson Plaza, Suite 300  
6600 Steubenville Pike  
Pittsburgh, PA, 15205  
United States  
T 412-494-4491  
[SDS@RescoProducts.com](mailto:SDS@RescoProducts.com) - [WWW.RescoProducts.com](http://WWW.RescoProducts.com)

#### 1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300  
Outside USA & Canada +1 703-741-5970

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2B	H320	Causes eye irritation
Carcinogenicity Category 1A	H350	May cause cancer (After drying or heating, Inhalation)

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



# Rescoset 10 CR TR-D3

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Gently wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms	: Dust when sawing or tear out. Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after inhalation	: After drying or heating. Dust when sawing or tear out. Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.

#### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: No unsuitable extinguishing media known.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Not flammable.
Explosion hazard	: Prolonged exposure to fire may cause containers to rupture/explode.
Reactivity in case of fire	: Fire conditions may produce small amounts of hexavalent chromium and other oxidation products.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire with normal precautions from a reasonable distance. Prevent fire-fighting water from entering environment..
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures	: If spilled, may cause the floor to be slippery.
----------------------	---

##### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Stop release.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Plug the leak, cut off the supply.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling	: Avoid contact with eyes. Avoid contact with skin.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in original container. Keep container closed when not in use.
Incompatible products	: Strong bases. Avoid contact with materials: such as sulfides and sulfites which could release toxic gases, mixing with strong bases because high heat of reaction can generate steam, and metals which could liberate hydrogen, a flammable gas.

# Rescoset 10 CR TR-D3

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Rescoset 10 CR TR-D3 (Mixture)

No additional information available

##### aluminium oxide, non-fibrous (1344-28-1)

###### USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA 1 mg/m<sup>3</sup> respirable dust

##### phosphoric acid, conc=75%, aqueous solution (7664-38-2)

No additional information available

##### chromium(III) oxide (1308-38-9)

No additional information available

##### quartz (14808-60-7)

###### USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA 0.025 mg/m<sup>3</sup> (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)

###### USA - OSHA - Occupational Exposure Limits

Local name Silica, crystalline quartz, respirable dust

OSHA PEL (TWA) [1] 0.05 mg/m<sup>3</sup> respirable dust

Remark (OSHA) (3) See Table Z-3.

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountain with clean water. After drying or heating. Dust when sawing or tear out. Provide adequate ventilation to minimize dust concentrations.

#### 8.3. Individual protection measures/Personal protective equipment

##### Personal protective equipment:

Avoid all unnecessary exposure.

##### Hand protection:

Wear protective gloves.

##### Eye protection:

Chemical goggles or safety glasses

##### Skin and body protection:

Wear suitable protective clothing

##### Respiratory protection:

After air drying or heating. Dust when sawing or tear out. Wear appropriate mask

##### Other information:

Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Slurry. Paste.
Color	: Green
Odor	: Acid Odor
Odor threshold	: No data available
pH	: < 3
Melting point	: > 2000 °F
Freezing point	: ≈ 32 °F
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: ≈ 2
Solubility	: Slightly soluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: Not Applicable

# Rescoset 10 CR TR-D3

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Fire conditions may produce small amounts of hexavalent chromium and other oxidation products.

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

No additional information available

### 10.5. Incompatible materials

Strong bases. Avoid contact with materials: such as sulfides and sulfites which could release toxic gases, mixing with strong bases because high heat of reaction can generate steam, and metals which could liberate hydrogen, a flammable gas.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### aluminium oxide, non-fibrous (1344-28-1)

LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))

#### phosphoric acid, conc=75%, aqueous solution (7664-38-2)

ATE US (oral)	4400 mg/kg body weight
---------------	------------------------

#### chromium(III) oxide (1308-38-9)

LD50 oral rat	> 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 5.41 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))

Skin corrosion/irritation : Causes skin irritation.  
pH: < 3

#### aluminium oxide, non-fibrous (1344-28-1)

pH	9 – 10.5 (aqueous suspension, 33 %)
----	-------------------------------------

#### phosphoric acid, conc=75%, aqueous solution (7664-38-2)

pH	0 – 0.5 (20 °C)
----	-----------------

#### chromium(III) oxide (1308-38-9)

pH	No data available in the literature
----	-------------------------------------

#### quartz (14808-60-7)

pH	6 – 7
----	-------

Serious eye damage/irritation : Causes eye irritation.  
pH: < 3

# Rescoset 10 CR TR-D3

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>aluminium oxide, non-fibrous (1344-28-1)</b>	
pH	9 – 10.5 (aqueous suspension, 33 %)
<b>phosphoric acid, conc=75%, aqueous solution (7664-38-2)</b>	
pH	0 – 0.5 (20 °C)
<b>chromium(III) oxide (1308-38-9)</b>	
pH	No data available in the literature
<b>quartz (14808-60-7)</b>	
pH	6 – 7
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (After drying or heating, Inhalation).
<b>quartz (14808-60-7)</b>	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: Not Applicable
<b>aluminium oxide, non-fibrous (1344-28-1)</b>	
Viscosity, kinematic	Not applicable (solid)
<b>chromium(III) oxide (1308-38-9)</b>	
Viscosity, kinematic	Not applicable (solid)
Potential Adverse human health effects and symptoms	: Dust when sawing or tear out. Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after inhalation	: After drying or heating. Dust when sawing or tear out. Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
<b>SECTION 12: Ecological information</b>	
<b>12.1. Toxicity</b>	
<b>aluminium oxide, non-fibrous (1344-28-1)</b>	
LC50 - Fish [1]	> 100 mg/l (96 h, Salmo trutta, Literature study)
EC50 - Crustacea [1]	> 100 mg/l (48 h, Daphnia magna, Literature study)
<b>chromium(III) oxide (1308-38-9)</b>	
LC50 - Fish [1]	> 10000 mg/l (ISO 7346-1, 96 h, Danio rerio, Static system, Fresh water, Experimental value, GLP)
<b>12.2. Persistence and degradability</b>	
<b>Rescoset 10 CR TR-D3 (Mixture)</b>	
Persistence and degradability	Not established.
<b>aluminium oxide, non-fibrous (1344-28-1)</b>	
Persistence and degradability	Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
<b>phosphoric acid, conc=75%, aqueous solution (7664-38-2)</b>	
Persistence and degradability	Biodegradability: not applicable.

# Rescoset 10 CR TR-D3

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>chromium(III) oxide (1308-38-9)</b>	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
<b>quartz (14808-60-7)</b>	
Persistence and degradability	Not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
<b>12.3. Bioaccumulative potential</b>	
<b>Rescoset 10 CR TR-D3 (Mixture)</b>	
Bioaccumulative potential	Not established.
<b>aluminium oxide, non-fibrous (1344-28-1)</b>	
Bioaccumulative potential	No data available.
<b>phosphoric acid, conc=75%, aqueous solution (7664-38-2)</b>	
Bioaccumulative potential	No test data of component(s) available.
<b>chromium(III) oxide (1308-38-9)</b>	
Bioaccumulative potential	Not bioaccumulative.
<b>quartz (14808-60-7)</b>	
Bioaccumulative potential	No data available.
<b>12.4. Mobility in soil</b>	
<b>aluminium oxide, non-fibrous (1344-28-1)</b>	
Surface tension	No data available in the literature
Ecology - soil	No data available.
<b>phosphoric acid, conc=75%, aqueous solution (7664-38-2)</b>	
Ecology - soil	Highly mobile in soil.
<b>chromium(III) oxide (1308-38-9)</b>	
Surface tension	No data available in the literature
Ecology - soil	Adsorbs into the soil.
<b>12.5. Other adverse effects</b>	
Effect on the global warming	: None known
Other information	: Avoid release to the environment.
<b>SECTION 13: Disposal considerations</b>	
<b>13.1. Disposal methods</b>	
Product/Packaging disposal recommendations	: Chromite (Cr <sup>+3</sup> ) may in normal use be converted chemically to a chromate (Cr <sup>+6</sup> ). Hexavalent chromium (Cr <sup>+6</sup> ) is considered a hazardous material.
Ecology - waste materials	: Avoid release to the environment.
<b>SECTION 14: Transport information</b>	
In accordance with DOT / TDG / IMDG / IATA <b>Department of Transportation (DOT)</b> In accordance with DOT Not regulated <b>Transportation of Dangerous Goods</b> Not regulated <b>Transport by sea</b> Not regulated <b>Air transport</b> Not regulated	
<b>SECTION 15: Regulatory information</b>	
<b>15.1. US Federal regulations</b>	
<b>Rescoset 10 CR TR-D3 (Mixture)</b>	
Note	This information must be included in all SDS's that are copied and distributed for this material.
All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory	
<b>aluminium oxide, non-fibrous (1344-28-1)</b>	
Not subject to reporting requirements of the United States SARA Section 313	

# Rescoset 10 CR TR-D3

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminium oxide, non-fibrous (1344-28-1)	
Note	Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.

phosphoric acid, conc=75%, aqueous solution (7664-38-2)	
Not subject to reporting requirements of the United States SARA Section 313	
CERCLA RQ	5000 lb

chromium(III) oxide (1308-38-9)	
Subject to reporting requirements of United States SARA Section 313	

### 15.2. International regulations

#### CANADA

aluminium oxide, non-fibrous (1344-28-1)	
Listed on the Canadian DSL (Domestic Substances List)	

phosphoric acid, conc=75%, aqueous solution (7664-38-2)	
Listed on the Canadian DSL (Domestic Substances List)	

chromium(III) oxide (1308-38-9)	
Listed on the Canadian DSL (Domestic Substances List)	

#### EU-Regulations

No additional information available

#### National regulations

quartz (14808-60-7)	
Listed on IARC (International Agency for Research on Cancer)	

### 15.3. US State regulations

Rescoset 10 CR TR-D3 (Mixture)	
U.S. - California - Proposition 65 - Other information	This product contains crystalline silica, a chemical known to the state of California to cause cancer. This product contains chromite (Cr <sup>+</sup> +3) which may in normal use, be converted chemically to a chromate (Cr <sup>+</sup> +6) hexavalent chrome, a chemical known to the State of California to cause cancer. For more information go to <a href="http://WWW.P65Warnings.ca.gov">WWW.P65Warnings.ca.gov</a>

quartz (14808-60-7)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component	State or local regulations
aluminium oxide, non-fibrous (1344-28-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
phosphoric acid, conc=75%, aqueous solution (7664-38-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
chromium(III) oxide (1308-38-9)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List
Quartz (14808-60-7)	U.S. - New Jersey - Right to Know Hazardous Substance List

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date

: 8/21/2024

Other information

: Report language name. English. In the event of any conflict between English and other language versions, the English version shall prevail.

Full text of H-phrases	
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H320	Causes eye irritation
H350	May cause cancer

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.