

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 3/15/2015 Revision date: 2/14/2025 Supersedes: 3/22/2022

SECTION 1: Identification					
1.1. Identification					
	: Mixture				
Product name	: Vibrocast 75				
CAS-No.	: Mixture				
Product code	: 0434 : Alumina-Silicate Cement Bonded Castable				
Other means of identification		Cement Bonded	Castable		
1.2. Recommended use and restrictions on u Use of the substance/mixture	: Refractory				
	: Industrial use				
1.3. Supplier					
RHI Magnesita One Robinson Plaza, Suite 300 6600 Steubenville Pike Pittsburgh, PA, 15205 United States T 412-494-4491 <u>SDS@RescoProducts.com</u> - <u>WWW.RescoProducts.com</u>	<u>om</u>				
1.4. Emergency telephone number					
Emergency number	: EMERGENCY C	ONLY (CHEMTRE Canada +1 703-7		Canada 1-800-4	424-9300
SECTION 2: Hazard(s) identification		Callaua +1 703-7	41-0970		
2.1. Classification of the substance or mixtu	re				
GHS-US classification					
Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2B Carcinogenicity, Category 1A Full text of H-statements: see section 16	ŀ	H320 C	auses skir auses eye lay cause		on).
2.2. GHS Label elements, including precaution	onary statement	ts			
GHS US labelling Hazard pictograms (GHS US)					
Signal word (GHS US) Hazard statements (GHS US) Precautionary statements (GHS US)	: P280 - Wear eye P305+P351+P33 contact lenses, if P332+P313 - If s	eye irritation se cancer (Inhala e protection, Dust	Respirato Rinse caut to do. Co urs: Get me	iously with wate ontinue rinsing. edical advice/atte	r for several minutes. Remove ention.
	P260 - Do not br	reathe dust.			
2.3. Other hazards which do not result in cla	ssification				
No additional information available					
2.4. Unknown acute toxicity (GHS US)					
No additional information available SECTION 3: Composition/information or	n ingradiante				
3.1. Substances					
Not applicable					
3.2. Mixtures					
Name		Product id	entifier	%	GHS-US classification
aluminum oxide, non-fibrous		CAS-No.: 13	844-28-1	50 – 75	Not classified
Calcium Aluminate Cement		CAS-No.: 65	997-16-2	5 – 10	Skin Irrit. 2, H315 Eye Irrit. 2B, H320
quartz		CAS-No.: 14	808-60-7	1 – 5	Carc. 1A, H350
cristobalite		CAS-No.: 14		0.1 – 0.5	Carc. 1A, H350
		1			, , ,

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements : see se	action 16
SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact First-aid measures after eye contact	<ul> <li>Gently wash with plenty of soap and water.</li> <li>IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present</li> </ul>
	and easy to do. Continue rinsing.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.
4.2. Most important symptoms and effects (	
Potential adverse human health effects and symptoms	: Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes eye irritation.
4.3. Immediate medical attention and specia	al treatment, if necessary
No additional information available	
SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguishing	
Suitable extinguishing media Unsuitable extinguishing media	<ul> <li>Use extinguishing media appropriate for surrounding fire.</li> <li>In case of fire, all extinguishing media allowed.</li> </ul>
5.2. Specific hazards arising from the chem	ical
Fire hazard	: Not flammable.
5.3. Special protective equipment and preca	autions for fire-fighters
Firefighting instructions	: Fight fire from safe distance and protected location. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
SECTION 6: Accidental release measure	es
6.1. Personal precautions, protective equip	ment and emergency procedures
6.1.1. For non-emergency personnel Emergency procedures	: Do not breathe dust. Avoid contact with skin and eyes.
6.1.2. For emergency responders	
Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area. On land, sweep or shovel into suitable containers.
6.2. Environmental precautions Prevent entry to sewers and public waters.	
6.3. Methods and material for containment a	and cleaning up
Methods for cleaning up	: On land, sweep or shovel into suitable containers. Minimise generation of dust.
6.4. Reference to other sections	
See Section 8. Exposure controls and personal prote	ction.
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Avoid raising dust. Avoid contact with skin and eves. Do not breathe dust.
Hygiene measures	
	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
7.2. Conditions for safe storage, including a	smoking and when leaving work.
Storage conditions	smoking and when leaving work. <b>Iny incompatibilities</b> : Store this product in a dry location where it can be protected from the elements.
Storage conditions Incompatible products	<ul> <li>smoking and when leaving work.</li> <li>incompatibilities</li> <li>Store this product in a dry location where it can be protected from the elements.</li> <li>Strong bases. Strong acids.</li> </ul>
Storage conditions Incompatible products SECTION 8: Exposure controls/persona	<ul> <li>smoking and when leaving work.</li> <li>incompatibilities</li> <li>Store this product in a dry location where it can be protected from the elements.</li> <li>Strong bases. Strong acids.</li> </ul>
Storage conditions Incompatible products SECTION 8: Exposure controls/persona 8.1. Control parameters	<ul> <li>smoking and when leaving work.</li> <li>incompatibilities</li> <li>Store this product in a dry location where it can be protected from the elements.</li> <li>Strong bases. Strong acids.</li> </ul>
Storage conditions Incompatible products SECTION 8: Exposure controls/persona 8.1. Control parameters cristobalite (14464-46-1)	<ul> <li>smoking and when leaving work.</li> <li>incompatibilities</li> <li>Store this product in a dry location where it can be protected from the elements.</li> <li>Strong bases. Strong acids.</li> </ul>
Storage conditions Incompatible products SECTION 8: Exposure controls/persona 8.1. Control parameters	<ul> <li>smoking and when leaving work.</li> <li>incompatibilities</li> <li>Store this product in a dry location where it can be protected from the elements.</li> <li>Strong bases. Strong acids.</li> </ul>

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

cristobalite (14464-46-1)	
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	0.05 mg/m <sup>3</sup> respirable dust
aluminum oxide, non-fibrous (1344-28-1)	
USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA	4 mar/m2 manipula duct
	1 mg/m <sup>3</sup> respirable dust
quartz (14808-60-7)	
USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA	0.005 ma/m² (Cilica Caustellina Questra LICA). Time uninted exercise currenture limit 0 to TLV
ACGIH OEL TWA	0.025 mg/m <sup>3</sup> (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
USA - OSHA - Occupational Exposure Limits	
Local name	Silica, crystalline quartz, respirable dust
OSHA PEL TWA	0.05 mg/m <sup>3</sup> respirable dust
Remark (OSHA)	(3) See Table Z-3.
8.2. Appropriate engineering controls	
Appropriate engineering controls	: Provide adequate ventilation to minimize dust concentrations.
8.3. Individual protection measures/Persona	
Personal protective equipment: Avoid all unnecessary exposure.	
Hand protection:	
Wear protective gloves.	
Eye protection:	
Chemical goggles or safety glasses	
Skin and body protection:	
Wear suitable protective clothing	
Respiratory protection:	
Wear appropriate mask	
Other information: Do not eat, drink or smoke during use.	
SECTION 9: Physical and chemical pro	perties
9.1. Information on basic physical and cher	nical properties
Physical state	: Solid
Appearance	: Granular mixture.
Colour	: Grey
Odour Odour threshold	: earthy : No data available
pH	: ≈ 10.5
pH solution concentration	: 10 %
Melting point	: > 3000 °F
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not flammable. : No data available
Vapour pressure Relative vapour density at 20°C	: No data available
Relative density	: ≈ 2.6
Solubility	: Slightly soluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	Not Applicable
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties Oxidising properties	: No data available : No data available
9.2. Other information No additional information available	

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity	
10.1. Reactivity	
Hydraulic setting.	
10.2. Chemical stability	
Stable under normal conditions of use.	
10.3. Possibility of hazardous reactions	
Not established.	
10.4. Conditions to avoid	
Avoid dust formation.	
10.5. Incompatible materials	
Strong acids. Strong bases.	
10.6. Hazardous decomposition products	
No additional information available	
SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
	: Not classified
Acute toxicity (dermal) Acute toxicity (inhalation)	: Not classified : Not classified
aluminum oxide, non-fibrous (1344-28-1)	1
LD50 oral rat	> 15900 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
Skin corrosion/irritation	Causes skin irritation.
	pH: ≈ 10.5
Calcium Aluminate Cement (65997-16-2)	
рН	≤ 13
cristobalite (14464-46-1)	
рН	6 – 7
aluminum oxide, non-fibrous (1344-28-1)	
pH	9 – 10.5 (aqueous suspension, 33 %)
- quartz (14808-60-7)	
PH	6-7
Serious eye damage/irritation	: Causes eye irritation. pH: ≈ 10.5
Calcium Aluminate Cement (65997-16-2)	
рН	≤ 13
cristobalite (14464-46-1)	
рН	6 - 7
aluminum oxide, non-fibrous (1344-28-1)	
pН	9 – 10.5 (aqueous suspension, 33 %)
quartz (14808-60-7)	
рН	6 – 7
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Inhalation).

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity STOT-single exposure STOT-repeated exposure Aspiration hazard Viscosity, kinematic	<ul> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> <li>Not Applicable</li> </ul>
aluminum oxide, non-fibrous (1344-28-1)	
Viscosity, kinematic	Not applicable (solid)
Potential adverse human health effects and symptoms Symptoms/effects after inhalation Symptoms/effects after skin contact Symptoms/effects after eye contact	<ul> <li>Danger of serious damage to health by prolonged exposure through inhalation.</li> <li>Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation.</li> <li>Causes skin irritation.</li> <li>Causes eye irritation.</li> </ul>
SECTION 12: Ecological information	
12.1. Toxicity	
aluminum oxide, non-fibrous (1344-28-1)	
LC50 - Fish [1]	> 100 mg/l (96 h, Salmo trutta, Literature study)
EC50 - Crustacea [1]	> 100 mg/l (48 h, Daphnia magna, Literature study)
12.2. Persistence and degradability	
Vibrocast 75 (Mixture)	
Persistence and degradability	Not established.
Calcium Aluminate Cement (65997-16-2)	
Persistence and degradability	Rapidly degradable
cristobalite (14464-46-1)	
Persistence and degradability	Mineral, Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
aluminum oxide, non-fibrous (1344-28-1)	
Persistence and degradability	Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
quartz (14808-60-7)	
Persistence and degradability	Not applicable.
Biochemical oxygen demand (BOD)	
	Not applicable
Chemical oxygen demand (COD)	Not applicable           Not applicable
Chemical oxygen demand (COD)	Not applicable
Chemical oxygen demand (COD) ThOD	Not applicable
Chemical oxygen demand (COD) ThOD 12.3. Bioaccumulative potential	Not applicable
Chemical oxygen demand (COD) ThOD 12.3. Bioaccumulative potential Vibrocast 75 (Mixture)	Not applicable         Not applicable

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminum oxide, non-fibrous (1344-28-1)				
Bioaccumulative potential	No data available.			
quartz (14808-60-7)				
Bioaccumulative potential	No data available.			
12.4. Mobility in soil				
cristobalite (14464-46-1)				
Ecology - soil	No data available.			
aluminum oxide, non-fibrous (1	344-28-1)			
Surface tension	No data available in the literature			
Ecology - soil	No data available.			
12.5. Other adverse effects				
Effect on global warming	: None known			
SECTION 13: Disposal consi	derations			
13.1. Disposal methods				
Product/Packaging disposal recommen	ndations : Dispose in a safe manner in accordance with local/national regulations.			
SECTION 14: Transport infor				
In accordance with DOT Not regulated Transportation of Dangerous Good Not regulated Transport by sea Not regulated Air transport Not regulated	ds			
	SECTION 15: Regulatory information			
15.1. US Federal regulations				
All components of this product are pre (TSCA) inventory	esent and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act			
aluminum oxide, non-fibrous (1	344-28-1)			
Not subject to reporting requirements of the United States SARA Section 313				
Note	Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.			
15.2. International regulations				
CANADA				
Calcium Aluminate Cement (65997-16-2)				
Listed on the Canadian DSL (Domestic Substances List)				
cristobalite (14464-46-1)				
Listed on the Canadian DSL (Domest	ic Substances List)			
aluminum oxide, non-fibrous (1344-28-1) Listed on the Canadian DSL (Domestic Substances List)				
LISTED OF THE CANADIAN DOL (DOMEST				

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations No additional information available

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations		
quartz (14808-60-7)		
Listed on IARC (International Agency for Research on Cancer)		
15.3. US State regulations		
Vibrocast 75 (Mixture)		
U.S California - Proposition 65 - Other information	This product contains crystalline silica, a chemical known to the state of California to cause cancer. For more information go to WWW.P65Warnings.ca.gov	

cristobalite (14464-46-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

quartz (14808-60-7)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component	State or local regulations
Cristobalite (14464-46-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous
, ,	Substance List; U.S Pennsylvania - RTK (Right to Know) List
aluminum oxide, non-fibrous (1344-28-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Quartz (14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List
SECTION 16: Other information	

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date Other information

- 2/14/2025 Report language name. English. In the event of any conflict between the English and other
- language versions, the English version shall prevail.

Full text of hazard classes and H-statements		
H315	Causes skin irritation.	
H320	Causes eye irritation	
H350	May cause cancer.	

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, RHI Magnesita makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.